

Fixed Dome Cameras

Features

- 1/3" Sony Super HAD CCD
- JBC-906D:
EIA: 510 x 492 / CCIR: 500 x 582 Pixels
- JBC-906HD:
EIA: 768 x 494 / CCIR: 752 x 582 Pixels
- 420 TV Lines (JBC-906D)
- 600 TV Lines (JBC-906HD)
- 0.1 Lux @F2.0 (JBC-906D)
- 0.2 Lux @F2.0 (JBC-906HD)
- AES / AGC
- 0.45 Gamma Correction
- 3.6mm/F2.0 Board Lens Built-in
- With Rotating Base Design for Easy Installation
- DC 12V
- Optional with Audio Output



JBC-906D
1/3" B/W Dome Cameras
JBC-906HD
1/3" High Res. B/W Dome Cameras

Specification

Model	JBC-906D	JBC906HD
Pick Up Element	1/3" SONY Super HAD CCD Sensor	
Picture Element	EIA: 510(H) x 492(V), CCIR: 500(H) x 582(V)	EIA: 768(H) x 494(V), CCIR: 752(H) x 582(V)
Horizontal Frequency	EIA: 15.734 KHz. ; CCIR: 15.625 KHz.	
Vertical Frequency	EIA: 59.94 Hz. ; CCIR: 50 Hz.	
Synchronization	Internal	
Scanning System	2 : 1 Interlace	
Resolution	Horizontal 420 TV Lines	Horizontal 600 TV Lines
Sensitivity	0.1 Lux @F2.0	0.2 Lux @F2.0
S/N Ratio	More than 48 dB (AGC Off)	
Gain Control	Automatic Gain Control	
Electronic Shutter	Auto: 1/60 (50) sec. ~ 1/100,000 sec.	
Gamma Correction	0.45	
Lens Built-in	3.6mm/F2.0 Lens	
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm	
Operating Temperature	- 10 ~ +50 degree C / RH 85% or less	
Power Consumption	Max. 1.2 W	
Power Supply	DC 12V	
Dimension	88mm (Dia.) x 63mm (H)	
Weight	200 Grams	
Optional Lens	2.5mm, 4.3mm, 6.0mm, 8.0mm, 12.0mm/F2.0 Board Lens	
Audio Output (Optional)	2.0 Vp-p / 50 Ohm, RCA Connector (Optional)	

Dimensions

