

# Fixed Dome Cameras

## Features

- 1/3" Sony Super HAD CCD Sensor
- NTSC: 811(H) x 508(V)  
PAL: 795(H) x 596(V)
- Horizontal 540 TV Lines
- 0.5 Lux @F2.0
- Auto Gain Control (AGC)
- Auto Electronic Shutter (AES)
- Auto White Balance (AWB)
- Auto Backlight Compensation
- 3.6mm/F2.0 Lens Built-in
- DC 12V
- Optional Lens with 2.5mm, 6.0mm, 8.0mm, 12.0mm & 16.0mm Lens

With Sony 10-bit HQ1 Digital Signal Processor Built-in



## JCC-918DHQ

1/3" Hi-Res. Color Dome Camera

## Specification

<b>Model</b>	JCC-918DHQ
<b>Pick Up Element</b>	1/3" Sony Super HAD CCD Sensor
<b>Digital Signal Processor</b>	Sony 10-bit HQ1 Digital Signal Processor (D.S.P.)
<b>Picture Element</b>	NTSC: 811(H) x 508(V) ; PAL: 795(H) x 596(V)
<b>Horizontal Frequency</b>	NTSC: 15.734 KHz. ; PAL: 15.625 KHz.
<b>Vertical Frequency</b>	NTSC: 59.94 Hz. ; PAL: 50 Hz.
<b>Synchronization</b>	Internal
<b>Scanning System</b>	2 : 1 Interlace
<b>Resolution</b>	Horizontal 540 TV Lines
<b>Sensitivity</b>	0.5 Lux @F2.0
<b>S/N Ratio</b>	More than 48 dB (AGC OFF)
<b>Gain Control</b>	Automatic Gain Control
<b>Electronic Shutter</b>	Auto: 1/60 (50) sec. ~ 1/100,000 sec.
<b>Lens Built-in</b>	3.6mm/F2.0 Board Lens
<b>White Balance</b>	Auto White Balance (3200K ~ 9200K)
<b>Video Output</b>	1.0 Vp-p Composite Video Output; 75 Ohms
<b>Lens Mount</b>	C/CS (with Ring Adapter)
<b>Operating Temperature</b>	- 10 ~ +50 degree C / RH 85% or less
<b>Power Consumption</b>	Max. 1.5 W
<b>Power Supply</b>	DC 12V
<b>Dimension</b>	112mm (Dia.) x 70mm (H)
<b>Weight</b>	220 grams
<b>Optional Lens</b>	2.5mm, 6.0mm, 8.0mm, 12.0mm, 16.0mm/F2.0 Board Lens

## Dimensions

