

B/W CCD Cameras

Box Cameras

Day/Night Cameras

Board Cameras

Dome Cameras

Network Solutions

PTZ Speed Domes

Features

- 1/3" LG B/W CCD Sensor
- EIA: 510 x 492 Pixels
CCIR: 500 x 582 Pixels
- 420 TV lines
- 0.2 Lux @ F1.2
- Auto Gain Control (AGC)
- AES On/Off Adjustable
- 0.45 Gamma Characteristic
- Accept Video & DC Iris
- C/CS Lens Mount
- Economic Design for Entry Level Applications
- DC 12V, AC 24V or AC 230V



JBC-384

1/3" Economic B/W CCD Camera

Specification

Model	JBC-384
Pick Up Element	1/3" LG B/W CCD Sensor
Picture Element	EIA: 510 (H) x 492 (V) ; CCIR: 500 (H) x 582 (V)
Horizontal Frequency	EIA: 15.734 KHz ; CCIR: 15.625 KHz
Vertical Frequency	EIA: 59.94 Hz ; CCIR: 50 Hz
Synchronization	Internal
Scanning System	2 : 1 Interlace
Resolution	Horizontal 420 TV lines
Sensitivity	0.2 Lux @ F=1.2
S/N Ratio	More than 48 dB (AGC Off)
Gain Control	Automatic Gain Control
Electronic Shutter	AUTO: 1/60 (50)sec.~ 1/120,000 sec ; OFF: 1/60 (50) sec.
Gamma Correction	0.45
Auto Iris	Accept Video & D.C Iris lens
Video Output	1.0 Vp-p Composite Video Output; 75 Ohms
Lens Mount	C/CS (with Ring Adapter)
Operating Temperature	- 10 ~ +50 degree C / RH 85% or less
Power Consumption	Max. 1.5 W
Power Supply	DC 12V, AC 24V or AC 230V
Dimension (W x H x D)	60mm x 48mm x 135mm
Weight	DC: 350 Grams, AC: 650 Grams

Dimensions

